

Han GND housing



Part number	09 14 001 0330
Specification	Han GND housing
HARTING eCatalogue	https://b2b.harting.com/09140010330

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Hoods/Housings
Series of hoods/housings	Han [®] GND
Type of hood/housing	Bulkhead mounted housing

Version

Locking type	Snap-in latches

Technical characteristics

Limiting temperature	-40 +85 °C
Note on the limiting temperature	For use as a connector according to IEC 61984.
Mating cycles	≥500
Degree of protection acc. to IEC 60529	IP65

Material properties

Material (hood/housing)	Polycarbonate (PC)
Colour (hood/housing)	Green
Material (seal)	NBR
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained

Page 1 / 2 | Creation date 2022-12-30 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



Material properties

REACH SVHC substances	Yes
REACH SVHC substances	6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol
California Proposition 65 substances	Yes
California Proposition 65 substances	Naphthalene
Specifications and approvals	
Chapilipations	IEC 60664-1
Specifications	IEC 61984
Commercial data	
Packaging size	1
Net weight	16.2 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140019027
eCl@ss	27440202 Shell for industrial connectors