

# D-Sub 15-pole MinD solder cup male nut M



Part number	09 67 015 1615
Specification	D-Sub 15-pole MinD solder cup male nut M
HARTING eCatalogue	https://b2b.harting.com/09670151615

Image is for illustration purposes only. Please refer to product description.

# Version

Termination method	Solder cup termination
Gender	Male
Size	D-Sub 2
Connection type	PCB to cable
	Cable to cable
Number of contacts	15
Locking type	Fixing flange with thread M3

#### Technical characteristics

recillical characteristics	
Conductor cross-section	0.5 mm²
Conductor cross-section	AWG 20
Rated current	7.5 A
Clearance distance	≥1 mm
Creepage distance	≥1 mm
Insulation resistance	>10 <sup>10</sup> Ω
Contact resistance	≤10 mΩ
Stripping length	2.5 3 mm
Tightening torque	≤0.6 Nm Female screw lock
Limiting temperature	-55 +125 °C
Insertion force	≤50 N
Withdrawal force	≥4.5 N ≤33 N
Performance level	2 acc. to CECC 75301-802

Page 1 / 3 | Creation date 2023-02-27 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application.

HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



# Technical characteristics

Mating cycles	≥250
Test voltage U <sub>r.m.s.</sub>	1 kV
Hot plugging	No

# Material properties

Material (insert)	Thermoplastic resin, glass-fibre filled (PBTP) Shell: steel, tin plated
Colour (insert)	White
Material (contacts)	Copper alloy
Surface (contacts)	Noble metal over Ni Mating side Sn over Ni Termination side
Material flammability class acc. to UL 94	V-0
RoHS	compliant with exemption
RoHS exemptions	6(a) / 6(a)-I: Lead as an alloying element in steel for machining purposes and in galvanised steel containing up to 0,35 % lead by weight / Lead as an alloying element in steel for machining purposes containing up to 0,35 % lead by weight and in batch hot dip galvanised steel components containing up to 0,2 % lead by weight 6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	ecef7555-f643-4ceb-a337-fc54762297f1
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead

# Specifications and approvals

Specifications	DIN 41652
UL / CSA	UL 1977 ECBT2.E102079

# Commercial data

Packaging size	100
Net weight	0.009 kg
Country of origin	Germany

Product data sheet 09 67 015 1615 D-Sub 15-pole MinD solder cup male nut M



# Commercial data

European customs tariff number	85366990
GTIN	5713140217317
eCl@ss	27440214 D-Sub coupler