

D SUB IP 67_15 POLE ANGLED



Part number	09 67 515 9658
Specification	D SUB IP 67_15 POLE ANGLED
HARTING eCatalogue	https://b2b.harting.com/09675159658

Image is for illustration purposes only. Please refer to product description.

Version

Termination method	Wave soldering termination
Gender	Male
Size	D-Sub 2
Number of contacts	15
further contacts	With grounding pin
PCB fixing	With board locks
Locking type	Fixing flange with thread M3

Technical characteristics

Distance between rows	2.54 mm
Contact spacing (termination side)	2.74 mm
Rated current	5 A
Clearance distance	≥1 mm
Creepage distance	≥1 mm
Insulation resistance	> 5 x 10 ⁹ Ω
Contact resistance	≤25 mΩ
Tightening torque	0.4 0.6 Nm Female screw lock
Limiting temperature	-25 +70 °C
Performance level	NM 30 (S4) 1
Mating cycles	≥500
Degree of protection acc. to IEC 60529	IP67
Test voltage U _{r.m.s.}	1.2 kV

Page 1 / 3 | Creation date 2023-03-02 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application.

HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



Technical characteristics

Isolation group	IIIa (175 ≤ CTI < 400)
PCB thickness	1.6 mm
Installation height	7.3 mm
Hot plugging	No

Material properties

Material (insert)	Thermoplastic resin, glass-fibre filled Shell: brass, tin plated
Colour (insert)	Red
Material (contacts)	Copper alloy
Surface (contacts)	Noble metal over Ni
Layer thickness	≥0.76 µm
Layer thickness	≥30 µinch
Material (seal)	Silicone
Colour (seal)	Red
Material	Thermoplastic resin, glass-fibre filled
Material flammability class acc. to UL 94	V-0
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
ELV status China RoHS	compliant with exemption 50
China RoHS	50
China RoHS REACH Annex XVII substances	50 Not contained
China RoHS REACH Annex XVII substances REACH ANNEX XIV substances	Not contained Not contained
China RoHS REACH Annex XVII substances REACH ANNEX XIV substances REACH SVHC substances	Not contained Not contained Yes
China RoHS REACH Annex XVII substances REACH ANNEX XIV substances REACH SVHC substances REACH SVHC substances	Not contained Not contained Yes Lead
China RoHS REACH Annex XVII substances REACH ANNEX XIV substances REACH SVHC substances REACH SVHC substances ECHA SCIP number	Not contained Not contained Yes Lead ecef7555-f643-4ceb-a337-fc54762297f1

Specifications and approvals

Specifications	DIN 41652
UL / CSA	UL 1977 ECBT2.E102079

Product data sheet 09 67 515 9658 D SUB IP 67_15 POLE ANGLED



Commercial data

Packaging size	50
Net weight	13.3 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140094475
eCl@ss	27440214 D-Sub coupler