



Pushing Performance  
Since 1945

# Han 24HPR VarioShell-4xM25-Set2



Image is for illustration purposes only. Please refer to product description.

Part number	10 40 124 1002
Specification	Han 24HPR VarioShell-4xM25-Set2
HARTING eCatalogue	<a href="https://b2b.harting.com/10401241002">https://b2b.harting.com/10401241002</a>

## Identification

Category	Hoods/Housings
Series of hoods/housings	Han® HPR VarioShell
Type of hood/housing	Complete set
Description of hood/housing	Angled

## Version

Size	24 HPR
Cable entry	for 1x 24 HPR 4x M32
Locking type	Screw locking
Field of application	Hoods/housings for harsh outdoor environments
Details	Please note the installation manual.
Pack contents	Bulkhead mounted housing Mounting cover 1x Bulkhead mounted housing 24 HPR enlarged Fixing screws

## Technical characteristics

Tightening torque	4 Nm Mounting cover 12 Nm Fixing screws 12 Nm PE screw
Limiting temperature	-40 ... +125 °C
Note on the limiting temperature	For use as a connector according to IEC 61984.



**Pushing Performance**  
Since 1945

## Technical characteristics

Degree of protection acc. to IEC 60529	IP66
	IP67
	IP68
	IP69

## Material properties

Material (hood/housing)	Aluminium die-cast Corrosion resistant
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 9005 (jet black)
Material (seal)	NBR
Material (locking)	Stainless steel

## Specifications and approvals

Specifications	IEC 61984
	IEC 61373 Category 1 Class B
CE	Yes

## Commercial data

Packaging size	1
Net weight	4,876 g
Country of origin	China
European customs tariff number	85389099
GTIN	5713140175600
eCl@ss	27440202 Shell for industrial connectors