

Han CGM-M M40x1,5 D.20-26mm/22-32mm



Image is for illustration purposes only. Please refer to product description.

| Part number | 19 00 000 5099 |
|--------------------|--|
| Specification | Han CGM-M M40x1,5 D.20-26mm/22-32mm |
| HARTING eCatalogue | https://b2b.harting.com/1900005099 |

Identification

| Category | Accessories |
|--------------------------|------------------------|
| Series of hoods/housings | Han [®] CGM-M |
| Type of accessory | Cable gland |

Technical characteristics

| Tightening torque | ≤15 Nm (depending on the cable and the seal insert used) |
|--|--|
| Wrench size | 50 |
| Limiting temperature | -40 +100 °C |
| Degree of protection acc. to IEC 60529 | IP68 IP69 / IPX9K acc. to ISO 20653 |
| Size | M40 |
| Clamping range | 20 32 mm |
| Width across corners | 55 mm |

Material properties

| Material (seal) | NBR |
|--------------------------|--|
| Material (cable glands) | Brass |
| Material (clamping ring) | Polyamide (PA) |
| Surface (accessories) | Nickel plated |
| RoHS | compliant with exemption |
| RoHS exemptions | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |



Material properties

| REACH Annex XVII substances | Not contained |
|--------------------------------------|---------------|
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Yes |
| REACH SVHC substances | Lead |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Lead |
| | Nickel |
| | Naphthalene |

Specifications and approvals

| UL / CSA | UL 514B QCRV.E479780 CSA-C22.2 No. 18.3 QCRV7.E479780 |
|-----------|--|
| Approvals | DNV GL |

Commercial data

| Commercial data | |
|--------------------------------|---|
| Packaging size | 1 |
| Net weight | 1 g |
| Country of origin | Germany |
| European customs tariff number | 84849000 |
| GTIN | 5713140123854 |
| eCl@ss | 27140801 Screwed cable gland (electrical) |
| | |