

Han 32A-HTE/HSE-M32



Image is for illustration purposes only. Please refer to product description.

Part number	19 20 032 0597
Specification	Han 32A-HTE/HSE-M32
HARTING eCatalogue	https://b2b.harting.com/19200320597

Identification

Category	Hoods/Housings
Series of hoods/housings	Han A [®]
Type of hood/housing	Hood
Type	High construction

Version

Size	32 A
Version	Top/side entry
Cable entry	1x M32 1x M32
Locking type	Double locking lever
Field of application	Standard Hoods/housings for industrial applications

Technical characteristics

Limiting temperature	-40 ... +125 °C
Note on the limiting temperature	For use as a connector according to IEC 61984.
Degree of protection acc. to IEC 60529	IP65
Type rating acc. to UL 50 / UL 50E	4 4X 12

Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Powder-coated



Pushing Performance
Since 1945

Material properties

Colour (hood/housing)	RAL 7037 (dust grey)
Material (seal)	NBR

Specifications and approvals

Approvals	DNV GL
CE	Yes

Commercial data

Packaging size	1
Net weight	189.28 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140164284
eCl@ss	27440202 Shell for industrial connectors