


PBZ connector with strain relief

Connector with strain, connection and fixation of the PL guide chains



Temperature: -40°C ... +135°C

Material: PA6 GFK plastics



FLEXA No.	Article	for Type	Bi [mm]	EO [mm]	G [mm]	F [mm]	Tiewrap plates	PU [Set]
1615404800	Connector with strain relief	PL4	48,0	60,0	6,1	30,0	5	1
1615506100	Connector with strain relief	PL5	61,0	75,0	6,1	45,0	5	1
1615508100	Connector with strain relief	PL5	81,0	95,0	6,1	55,0	7	1
1615303100	Connector with strain relief PBZ	PL3	31,0	41,0	6,5	10,0	3	1
1615403800	Connector with strain relief	PL4	38,0	50,0	6,1	22,0	3	1
1615511100	Connector with strain relief	PL5	111,0	125,0	6,1	80,0	9	1
1615406800	Connector with strain relief	PL4	68,0	80,0	6,1	44,0	7	1

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.