


SCSRN strain relief bar

Strain relief bar for heavy-duty applications, for mounting to PB standard connector



Temperature: -40°C ... +135°C

Material: galvanized steel



FLEXA No.	Article	for Type	C profile	H [mm]	B [mm]	Length [mm]	PU [pcs.]
16271200000	Strain relief bar	PH 10/12	12,0		28,0	200,0	1
16277100000	Strain relief bar	PH 7	11,0		25,0	100,0	1
16271350000	Strain relief bar	PH 10/12	12,0		28,0	350,0	1
16277200000	Strain relief bar	PH 7	11,0		25,0	200,0	1
16271100000	Strain relief bar	PH 10/12	12,0		28,0	100,0	1
16271300000	Strain relief bar	PH 10/12	12,0		28,0	300,0	1
16277065000	Strain relief bar	PH 7	11,0		25,0	65,0	1
16271150000	Strain relief bar	PH 10/12	12,0		28,0	150,0	1
16271250000	Strain relief bar	PH 10/12	12,0		28,0	250,0	1
16277050000	Strain relief bar	PH 7	11,0		25,0	50,0	1
16271075000	Strain relief bar	PH 10/12	12,0		28,0	75,0	1
16277150000	Strain relief bar	PH 7	11,0		25,0	150,0	1

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.