

## Uni-Dicht-Verschraubung Pg36, 32-36mm



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| Part number        | 09 00 000 5099                                                                        |
| Specification      | Uni-Dicht-Verschraubung Pg36, 32-36mm                                                 |
| HARTING eCatalogue | <a href="https://b2b.harting.com/09000005099">https://b2b.harting.com/09000005099</a> |

### Identification

|                   |             |
|-------------------|-------------|
| Category          | Accessories |
| Type of accessory | Cable gland |

### Technical characteristics

|                                        |                                                          |
|----------------------------------------|----------------------------------------------------------|
| Tightening torque                      | ≤30 Nm (depending on the cable and the seal insert used) |
| Wrench size                            | 50                                                       |
| Limiting temperature                   | -40 ... +130 °C                                          |
| Degree of protection acc. to IEC 60529 | IP68                                                     |
| Size                                   | Pg 36                                                    |
| Clamping range                         | 32 ... 36 mm                                             |

### Material properties

|                                      |                                                        |
|--------------------------------------|--------------------------------------------------------|
| Material (cable glands)              | Metal                                                  |
| Colour (accessories)                 | Pink                                                   |
| RoHS                                 | compliant with exemption                               |
| RoHS exemptions                      | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status                           | compliant with exemption                               |
| China RoHS                           | 50                                                     |
| REACH Annex XVII substances          | Not contained                                          |
| REACH ANNEX XIV substances           | Not contained                                          |
| REACH SVHC substances                | Yes                                                    |
| REACH SVHC substances                | Lead                                                   |
| California Proposition 65 substances | Yes                                                    |



Pushing Performance  
Since 1945

Material properties

|                                      |        |
|--------------------------------------|--------|
| California Proposition 65 substances | Lead   |
|                                      | Nickel |

Commercial data

|                                |                                           |
|--------------------------------|-------------------------------------------|
| Packaging size                 | 1                                         |
| Net weight                     | 147.5 g                                   |
| Country of origin              | Germany                                   |
| European customs tariff number | 84849000                                  |
| GTIN                           | 5713140001800                             |
| eCl@ss                         | 27140801 Screwed cable gland (electrical) |