

Han module adapter, male



Part number	09 14 001 3011
Specification	Han module adapter, male
HARTING eCatalogue	https://b2b.harting.com/09140013011

Image is for illustration purposes only. Please refer to product description.

Version

Gender	Male
Technical characteristics	
Insulation resistance	>10 ¹⁰ Ω
Limiting temperature	-40 +85 °C
Material properties	
Material (insert)	Polycarbonate (PC)
Colour (insert)	RAL 7032 (pebble grey)
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Not contained
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R22 (HL 1-3) R23 (HL 1-3)

Specifications and approvals

Specifications	IEC 60664-1
	IEC 61984

Page 1 / 2 | Creation date 2023-03-03 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany

Product data sheet 09 14 001 3011 Han module adapter, male



Specifications and approvals

UL 1977 ECBT2.E235076
DNV GL
2
5.65 g
Germany
85389099
5713140019317
27440207 Adapter for industrial connectors (module/contact insert)

Page 2 / 2 | Creation date 2023-03-03 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany