

## Han-Quintax contact female, 3-9.5mm



Image is for illustration purposes only. Please refer to product description.

Part number	09 15 004 3113 XL
Specification	Han-Quintax contact female, 3-9.5mm
HARTING eCatalogue	<a href="https://b2b.harting.com/09150043113XL">https://b2b.harting.com/09150043113XL</a>

### Identification

Category	Inserts
Series	Han-Quintax®
Description of the contact	for Han D® crimp contacts

### Version

Gender	Female
Number of contacts	4
further contacts	+ shielding
Details	Please order crimp contacts separately.

### Technical characteristics

Conductor cross-section	0.14 ... 2.5 mm²
Rated current	10 A
Rated voltage	50 V
Rated impulse voltage	0.8 kV
Pollution degree	3
Contact resistance, shielding	≤100 mΩ
Limiting temperature	-40 ... +85 °C
Mating cycles	≥500

### Material properties

Material (insert)	Polycarbonate (PC)
Colour (insert)	RAL 7032 (pebble grey)



**Pushing Performance**  
Since 1945

## Material properties

Material (shielding)	Zinc die-cast, nickel-plated
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained

## Specifications and approvals

Specifications	IEC 60664-1 IEC 61984
UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076

## Commercial data

Packaging size	400
Net weight	26.18 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140187856
eCl@ss	27440218 Module for industrial connectors (data)