

Han 16B-HBM single lever metal cover



Part number	09 30 016 0318
Specification	Han 16B-HBM single lever metal cover
HARTING eCatalogue	https://b2b.harting.com/09300160318

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Hoods/Housings
Series of hoods/housings	Han [®] B
Type of hood/housing	Bulkhead mounted housing
Description of hood/housing	With metal cover
Туре	Low construction

Version

Size	16 B
Locking type	Single locking lever
Han-Easy Lock [®]	Yes
Field of application	Standard hoods/housings for industrial connectors

Technical characteristics

Limiting temperature	-40 +125 °C
Note on the limiting temperature	For use as a connector according to IEC 61984.
Degree of protection acc. to IEC 60529	IP65
Type rating acc. to UL 50 / UL 50E	4
	4X
	12

Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 7037 (dust grey)

Page 1 / 2 | Creation date 2023-03-17 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application.

HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



Material properties

Material (locking)	olycarbonate (PC) tainless steel
Colour (locking) R	AL 7037 (dust grey)
Material flammability class acc. to UL 94 (locking levers)	-0
RoHS cc	ompliant
ELV status co	ompliant
China RoHS e	
REACH Annex XVII substances No	ot contained
REACH ANNEX XIV substances No	ot contained
REACH SVHC substances Ye	es
REACH SVHC substances	,6'-di-tert-butyl-2,2'-methylenedi-p-cresol otassium 1,1,2,2,3,3,4,4,4-nonafluorobutane-1-sulphonate
ECHA SCIP number 16	6ca3004-52e6-46fa-bf13-9c1e1b30f813
California Proposition 65 substances Ye	es
California Proposition 65 substances	ickel aphthalene
Fire protection on railway vehicles	N 45545-2 (2020-08)
Requirement set with Hazard Levels	22 (HL 1-3) 23 (HL 1-3)

Specifications and approvals

UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076
CE	Yes
Approvals	DNV GL

Commercial data

Packaging size	1
Net weight	179 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140045712
eCl@ss	27440202 Shell for industrial connectors