

	9=	
	Part number	09 30 016 1260
	Specification	Han B Base SM LC 4 Pegs plast cover Pg21
	HARTING eCatalogue	https://b2b.harting.com/09300161260

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Hoods/Housings	
Series of hoods/housings	Han [®] B	
Type of hood/housing	Surface mounted housing	
Description of hood/housing	With thermo-plastic cover	
Туре	Low construction	
Version		
Size	16 B	
Version	Side entry	
Cable entry	2x Pg 21	

Locking type	Double locking lever (on the hood)

Standard hoods/housings for industrial connectors

Technical characteristics

Field of application

Limiting temperature	-40 +125 °C
Note on the limiting temperature	For use as a connector according to IEC 61984.
Degree of protection acc. to IEC 60529	IP65
	4
Type rating acc. to UL 50 / UL 50E	4X
	12

Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Powder-coated

Page 1 / 2 | Creation date 2023-01-27 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany

Han B Base SM LC 4 Pegs plast cover Pg21



Material properties

Colour (hood/housing)	RAL 7037 (dust grey)		
Material (seal)	NBR		
RoHS	compliant		
ELV status	compliant		
China RoHS	e		
REACH Annex XVII substances	Not contained		
REACH ANNEX XIV substances	Not contained		
REACH SVHC substances	Yes		
REACH SVHC substances	6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol		
ECHA SCIP number	5b0b428a-c671-4c90-9b6d-16804ea5737a		
California Proposition 65 substances	Yes		
California Proposition 65 substances	Lead Nickel Naphthalene		
Fire protection on railway vehicles	EN 45545-2 (2020-08)		
Requirement set with Hazard Levels	R1 (HL 1-3) R7 (HL 1-3)		
Specifications and approvals			
Approvals	DNV GL		
CE	Yes		
Commercial data			
Packaging size	1		
Net weight	255 g		
Country of origin	Germany		

Country of originGermanyEuropean customs tariff number85389099GTIN5713140046153eCl@ss27440202 Shell for industrial connectors

Page 2 / 2 | Creation date 2023-01-27 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany