

PP-V14-CC-IDC-RJ45-8P-P-M-ANG-BOT-SHLD



Part number	09 35 220 0402
Specification	PP-V14-CC-IDC-RJ45-8P-P-M-ANG-BOT-SHLD
HARTING eCatalogue	https://b2b.harting.com/09352200402

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Connectors
Series	Han [®] PushPull (V14)
Element	Connector
Charification	AIDA compliant
Specification	PROFINET
Specification	PROFINET Multi Feature RJ45
Specification	

Version

Termination method	IDC termination
Shielding	Fully shielded, 360° shielding contact
Number of contacts	8
Coding	RJ45

Technical characteristics

Conductor cross-section	0.12 0.32 mm ² Stranded 0.12 0.32 mm ² Solid
Conductor cross-section	AWG 26/7 AWG 22/7 Stranded AWG 24/1 AWG 22/1 Solid
Wire outer diameter	0.8 1.6 mm
Transmission characteristics	Cat. 6 _A Class E _A up to 500 MHz



Technical characteristics

Data rate	10 Mbit/s
	100 Mbit/s
	1 Gbit/s
Data Tate	2.5 Gbit/s
	5 Gbit/s
	10 Gbit/s
Limiting temperature	-40 +85 °C
Mating cycles	≥750
D () () () () () () () () () (IP65
Degree of protection acc. to IEC 60529	IP67
Cable diameter	6.5 9.5 mm

Material properties

Surface (contacts)	Au over Ni Mating side Sn over Ni Termination side
Material (hood/housing)	Zinc die-cast
Surface (hood/housing)	Nickel plated
RoHS	compliant
ELV status	compliant
China RoHS	е
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol
ECHA SCIP number	5b0b428a-c671-4c90-9b6d-16804ea5737a
California Proposition 65 substances	Not contained

Specifications and approvals

Specifications	IEC 60603-7 Mating face ISO/IEC 11801 EN 50173-1 IEC 61076-3-117 Variant 14
Approvals	DNV GL
PROFINET	Yes

Commercial data

Packaging size	1	
----------------	---	--

Product data sheet 09 35 220 0402 PP-V14-CC-IDC-RJ45-8P-P-M-ANG-BOT-SHLD



Commercial data

Net weight	93.75 g
Country of origin	Latvia
European customs tariff number	85366990
GTIN	5713140224285
eCl@ss	27440114 Rectangular connector (for field assembly)