

Han 16B Ex-HBM-Double Lever



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 09 36 016 1301 |
| Specification | Han 16B Ex-HBM-Double Lever |
| HARTING eCatalogue | https://b2b.harting.com/09360161301 |

Version

| | |
|----------------------|--|
| Size | 16 B |
| Locking type | Double locking lever |
| Field of application | Connectors for explosion hazardous environments |
| Details | ATTENTION! Only to be used with Han [®] Ex inserts! |

Technical characteristics

| | |
|--|--|
| Limiting temperature | -20 ... +40 °C |
| Note on the limiting temperature | For use as a connector according to IEC 61984. |
| Degree of protection acc. to IEC 60529 | IP65 With cable gland |

Material properties

| | |
|-----------------------------|--|
| Material (hood/housing) | Zinc die-cast |
| Surface (hood/housing) | Powder-coated |
| Colour (hood/housing) | RAL 5015 (sky blue) |
| Material (seal) | NBR |
| Material (locking) | Stainless steel |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Yes |
| REACH SVHC substances | 6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol |



Pushing Performance
Since 1945

Material properties

| | |
|--------------------------------------|-------------|
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Lead |
| | Nickel |
| | Naphthalene |

Commercial data

| | |
|--------------------------------|--|
| Packaging size | 1 |
| Net weight | 274 g |
| Country of origin | China |
| European customs tariff number | 85389099 |
| GTIN | 5713140054912 |
| eCl@ss | 27440202 Shell for industrial connectors |