


# RJI DB Cat6a Cable Assy green PUR 3,0m



Part number	09 48 474 7744 030
Specification	RJI DB Cat6a Cable Assy green PUR 3,0m
HARTING eCatalogue	https://b2b.harting.com/09484747744030

Image is for illustration purposes only. Please refer to product description.

#### Identification

Category	System cabling
Series	RJ45
Element	Cable assemblies
Specification	Pre-assembled on both sides
Connector 1	HARTING DualBoot RJ45
Connector 2	HARTING DualBoot RJ45
Type of cable	Copper cable (round)
Version	
Cable length	3 m
Number of cores	8
Core structure	4x 2x AWG 26/7
Technical characteristics	
Transmission characteristics	Cat. 6 <sub>A</sub> Class E <sub>A</sub> up to 500 MHz
Data rate	10 Mbit/s 100 Mbit/s 1 Gbit/s 2.5 Gbit/s 5 Gbit/s 10 Gbit/s
Limiting temperature	-40 +80 °C unmoved -40 +80 °C moved

Page 1 / 2 | Creation date 2023-01-13 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Customised Solutions GmbH & Co. KG | In der Tütenbeke 22 | 32339 Espelkamp | Germany Phone +49 5772 47-0 | info@HARTING.com | www.HARTING.com



#### Material properties

Material (cable)	PUR (polyurethane)
Colour (cable)	Green
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained

## Specifications and approvals

Specifications	IEC 60332-1-2 Flame retardancy IEC 60754-1 Halogen freeness
	EN 60811-404 Oil resistance
	UN/ECE-R 118 fire protection for rolling stock
UL / CSA	UL 1863 DUXR.E470046

### Commercial data

Packaging size	1
Net weight	160 g
Country of origin	Czechia
European customs tariff number	85444290
GTIN	5713140256088
eCl@ss	27060308 Patch cord copper (data cable)