

Set PP Metal receptacle MM GOF adapter



| Part number | 09 57 468 0500 000 |
|--------------------|--|
| Specification | Set PP Metal receptacle MM GOF adapter |
| HARTING eCatalogue | https://b2b.harting.com/09574680500000 |

Image is for illustration purposes only. Please refer to product description.

Identification

| Category | Connectors |
|-----------------------------|-----------------------|
| Series | HARTING PushPull (V4) |
| Identification | LC duplex |
| Element | Panel feed trough set |
| Description of the contact | Multimode |
| Description of hood/housing | EasyInstall |

Version

| Number of contacts | 2 |
|--------------------|----------|
| Locking type | PushPull |

Technical characteristics

| Limiting temperature | -40 +70 °C |
|--|------------|
| Mating cycles | ≥200 |
| Degree of protection acc. to IEC 60529 | IP65 |

Material properties

| Material (hood/housing) | Metal |
|---|---------------|
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | е |
| REACH Annex XVII substances | Not contained |



Material properties

| REACH ANNEX XIV substances | Not contained |
|--------------------------------------|---|
| REACH SVHC substances | Not contained |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Antimony trioxide Lead Nickel Naphthalene |
| Requirement set with Hazard Levels | R26 |

Specifications and approvals

| Specifications | IEC 61076-3-106 Variant 4 (V4) |
|----------------|--------------------------------|
| Approvals | DNV GL |

Commercial data

| Packaging size 1 |
|--|
| i ackaying size |
| Net weight 27 g |
| Country of origin Romania |
| European customs tariff number 85366990 |
| GTIN 5713140223790 |
| eCl@ss 27440114 Rectangular connector (for field assembly) |