

## Han 10M-HSM2-HC-f. DL-M32-M32 bottom



Image is for illustration purposes only. Please refer to product description.

Part number	19 37 010 0294
Specification	Han 10M-HSM2-HC-f. DL-M32-M32 bottom
HARTING eCatalogue	<a href="https://b2b.harting.com/19370100294">https://b2b.harting.com/19370100294</a>

### Identification

Category	Hoods/Housings
Series of hoods/housings	Han <sup>®</sup> M
Type of hood/housing	Surface mounted housing
Type	High construction

### Version

Size	10 B
Version	Side entry
Cable entry	3x M32
Locking type	Double locking lever
Field of application	Hoods/housings for rough environments

### Technical characteristics

Limiting temperature	-40 ... +125 °C
Note on the limiting temperature	For use as a connector according to IEC 61984.
Degree of protection acc. to IEC 60529	IP65
Type rating acc. to UL 50 / UL 50E	4 4X 12

### Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 9005 (jet black)



**Pushing Performance**  
Since 1945

## Material properties

Material (seal)	FPM
Material (locking)	Stainless steel

## Specifications and approvals

Approvals	DNV GL
UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076
CE	Yes

## Commercial data

Packaging size	1
Net weight	357.92 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140171152
eCl@ss	27440202 Shell for industrial connectors