

Part number

MFON 16.32



Hood, LS-TYPE series, with 4 pegs, M32 side cable entry without adapter, size "77.27", high construction

Product description

Product type	Hood
Series	LS-TYPE
Closing type	With 4 pegs
Size	Size "77.27"
Cable entry	Side cable entry M32
Specification	High construction

Technical data

IP degree of protection	IP65 / IP66 / IP69
--------------------------------	--------------------

Further technical details

Weight	258,00 g
Operating temperature range (min, max)	-40°C...+125°C

Material properties

Colour	RAL 9005 black
RoHs conformity	Compliant
China RoHs - EFUP	E
REACH SVHC substances	No

Approvals / Standards

Certifications	DNV, BV
UL	ECBT2
cUL	ECBT8

General ordering information

EAN13 code	8015747044295
eCl@ss 8.1	27440202
ETIM 7.0	EC000437

Packaging Information


Packaging length	175,00 mm
Packaging height	195,00 mm
Packaging width	260,00 mm
Packaging weight	2,46 kg
Packaging volume	8,87 dm³
Packaging description	Carton box
Packaging quantity	20 Pcs
Packaging EAN code	8015747187732
Sub-packaging weight	0,62 kg
Sub-packaging description	Plastic packaging
Sub-packaging quantity	5 Pcs
Sub-packaging EAN barcode	8015747187749

Part number

MFON 16.32



Catalogue drawings



Catalogue drawings

CH..N - MA, MF..N enclosures

size "77.27"

LS-TYPE version

inserts:

CD	40 poles + @	49+52 *
CT, CTS **)	40 poles + @	56 *
CDD	72 poles + @	62+65 *
CQE	32 poles + @	82+84 *
CSH	16 poles + @	90+92 *
CCE	16 poles + @	98+102 *
CNE, CSE, JCNE, JCSE	16 poles + @	99 and 108 *
CSS	16 poles + @	120+122 *
CTE, CTSE **)	16 poles + @	128 *
CMSE	6+2 (aux) poles + @	137 *
CMCE	6+2 (aux) poles + @	136 *
CP	6 poles + @	149+150 *
CX	6/36 e 12/2 poles + @	152+153 *
CX	4/0 e 4/2 poles + @	154 *
MIXO	4 modules	160+195 *

insert centre distance: 77,5 x 27 mm

* refer to catalogue page CN.12

description	part no.	entry M
bulkhead mounting housing, with 2 levers	CHIN 16	
surface mounting housing, high construction, with 2 levers	MAPN 16.32	32
with pegs, side entry		
with pegs, side entry, high construction		
with pegs, top entry		
with pegs, top entry, high construction		

**) only in the CHIN 16 enclosure

panel cut-out for bulkhead mounting housing in mm

- kiln powder coating with RAL 9005 black epoxy polyester powder

- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

dimensions shown are not binding and may be changed without notice

dimensions in mm

CHIN 16

MAPN 16.32

dimensions in mm

MFON 16.32

MFVN 16.32

MHON 16.32

MHVN 16.32

Notes

Dimensions shown in mm are not binding and may be changed without notice.