

Part number

MFVN 10 G32



Hood, LS-TYPE series, with 2 levers, M32 top cable entry without adapter, size "57.27", high construction

Product description

Product type	Hood
Series	LS-TYPE
Closing type	With 2 levers
Size	Size "57.27"
Cable entry	Top cable entry M32
Specification	High construction

Technical data

IP degree of protection	IP65 / IP66 / IP69
--------------------------------	--------------------

Further technical details

Weight	310,00 g
Operating temperature range (min, max)	-40°C...+125°C

Material properties

Colour	RAL 9005 black
RoHs conformity	Compliant
China RoHs - EFUP	E
REACH SVHC substances	No

Approvals / Standards

Certifications	DNV, BV
UL	ECBT2
cUL	ECBT8

General ordering information

EAN13 code	8015747187404
eCl@ss 8.1	27440202
ETIM 7.0	EC000437

Packaging Information


Sub-packaging weight	1,55 kg
Sub-packaging description	Plastic packaging
Sub-packaging quantity	5 Pcs
Sub-packaging EAN barcode	8015747188166

Part number

MFVN 10 G32



Catalogue drawings



Catalogue drawings

CH..N - MF..N enclosures

size "57.27"

LS-TYPE version

inserts:

CDD	42 poles + @	61 *
CQE	18 poles + @	81 *
CSH	10 poles + @	89 *
CCE	10 poles + @	90 *
CNE, CSE, JCNE, JCSE	10 poles + @ 97 and 107 *	
CSS	10 poles + @	119 *
CMSE	3+2 (aux) poles + @	135 *
CMCE	3+2 (aux) poles + @	134 *
CX	8/24 poles + @	151 *
MIXO	3 modules	160+195 *

insert centre distance: 57 x 27 mm

* refer to catalogue page CN.12

hoods with 4 pegs

covers

description	part no.	entry M	part no.
with 2 levers and gasket, top entry	MHVN 10 G25	25	CHCN 10
with 2 levers and gasket, top entry, high construction	MFVN 10 G32	32	CHCN 10 G
covers with pegs			
covers with 2 levers			

dimensions in mm

MHVN 10 G25

MFVN 10 G32

dimensions in mm

CHCN 10

CHCN 10 G

- kiln powder coating with RAL 9005 black epoxy polyester powder

- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

IP65

dimensions shown are not binding and may be changed without notice

Notes

Dimensions shown in mm are not binding and may be changed without notice.