

Part number

MFVN 24.32



Hood, LS-TYPE series, with 4 pegs, M32 top cable entry without adapter, size "104.27", high construction

Product description

Product type	Hood
Series	LS-TYPE
Closing type	With 4 pegs
Size	Size "104.27"
Cable entry	Top cable entry M32
Specification	High construction

Technical data

IP degree of protection	IP65 / IP66 / IP69
--------------------------------	--------------------

Further technical details

Operating temperature range (min, max)	-40°C...+125°C
---	----------------

Material properties

Colour	RAL 9005 black
RoHs conformity	Compliant
China RoHs - EFUP	E
REACH SVHC substances	No

Approvals / Standards

Certifications	DNV, BV
UL	ECBT2
cUL	ECBT8

General ordering information

EAN13 code	8015747163606
eCl@ss 8.1	27440202
ETIM 7.0	EC000437

Packaging Information


Sub-packaging description	Plastic packaging
Sub-packaging quantity	5 Pcs
Sub-packaging EAN barcode	8015747187824

Part number

MFVN 24.32



Catalogue drawings



Catalogue drawings

CH..N - MA, MF..N enclosures

size "104.27"

LS-TYPE version

inserts:

CD	64 poles + @	51+53 *
CT, CTS **)	64 poles + @	57 *
CDD	108 poles + @	64+66 *
CQE	46 poles + @	83+85 *
CSH	24 poles + @	91+93 *
CCE	24 poles + @	100+104 *
CNE, CSE, JCNE, JCSE	24 poles + @	101 and 109 *
CSS	24 poles + @	122+123 *
CTE, CTSE **)	24 poles + @	129 *
CMSE	10+2 (aux) poles + @	139 *
CMCE	10+2 (aux) poles + @	138 *
CX	4/8 poles + @	155 *
MIXO	6 modules	160+195 *

insert centre distance: 104 x 27 mm

* refer to catalogue page CN.12

housings with double lever

hoods with 4 pegs

description	part no.	entry M	part no.	entry M
bulkhead mounting housing, with 2 levers	CHIN 24			
surface mounting housing, high construction, with 2 levers	MAPN 24.32	32		
with pegs, side entry			MHON 24.32	32
with pegs, side entry, high construction			MFON 24.32	32
with pegs, side entry			MHVN 24.32	32
with pegs, side entry, high construction			MFVN 24.32	32

** only in the CHIN 24 enclosure

panel cut-out for bulkhead mounting housing in mm

- kiln powder coating with RAL 9005 black epoxy polyester powder

- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

IP65

dimensions shown are not binding and may be changed without notice

dimensions in mm

CHIN 24

MAPN 24.32

dimensions in mm

MFON 24.32

MFVN 24.32

MHON 24.32

MHVN 24.32

Notes

Dimensions shown in mm are not binding and may be changed without notice.