### Part number

protection

Weight

**Further technical details** 

# MNZ 24 PO





Complete connector, CNZ series, composed of 2 screw terminal connection inserts with 24 poles + PE, and surface mounting housing with 2 levers and hood with side cable entry

Product description	
Product type	Complete connector
Series	CNZ
Connection type	Screw terminal connection
Size	Size "104.27"
N. of poles	24 poles + 🖶
Cable entry	M25/32
Specification	Surface mounting housing with 2 levers and hood with side cable entry
Technical data	
Current	16 A
Voltage	500 V
Rated impulse withstand voltage	6 kV
Pollution degree	3
Wire cross-section	0,50 mm <sup>2</sup> - 2,50 mm <sup>2</sup>
AWG size	20 - 14
Contact type	Turned silver plated
IP degree of	IP65 / IP66 / IP69

910,00 g

	Material properties		
	Colour	RAL 7040 grey	
	SCIP number	A54fce24-f9c5-479f-a7e4- adb75fec7abe	
	Approvals / Standards		
	Reference standard	EN 61984:2009-06	
	Certifications	EAC	
	General ordering information		
	EAN13 code	8015747059237	
Packaging Information			
	Packaging length	335,00 mm	
	Packaging height	320,00 mm	
	Packaging width	400,00 mm	
	Packaging weight	18,20 kg	
	Packaging volume	42,88 dm³	
	Packaging description	Carton box	
	Packaging quantity	20 Pcs	
	Packaging EAN code	8015747109758	
	Sub-packaging weight	0,91 kg	
	Sub-packaging description	Plastic bag	
	Sub-packaging quantity	1 Pcs	
	Sub-packaging EAN barcode	8015747223812	

### Part number

## MNZ 24 PO



### **Notes**

Dimensions shown in mm are not binding and may be changed without notice.

#### **California Proposition 65 Information**



WARNING

This product can expose you to lead and its compounds, known to the State of California to cause cancer and/or reproductive toxicity. For more information go to www.P65Warnings.ca.gov.