


Part number

MNZ 24 PV



Complete connector, CNZ series, composed of 2 screw terminal connection inserts with 24 poles + PE, and surface mounting housing with 2 levers and hood with top cable entry

Product description

Product type	Complete connector
Series	CNZ
Connection type	Screw terminal connection
Size	Size "104.27"
N. of poles	24 poles + 
Cable entry	M25/32
Specification	Surface mounting housing with 2 levers and hood with top cable entry

Technical data

Current	16 A
Voltage	500 V
Rated impulse withstand voltage	6 kV
Pollution degree	3
Wire cross-section	0,50 mm ² - 2,50 mm ²
AWG size	20 - 14
Contact type	Turned silver plated
IP degree of protection	IP65 / IP66 / IP69

Further technical details

Weight	80,00 g
---------------	---------

Material properties

Colour	RAL 7040 grey
SCIP number	A54fce24-f9c5-479f-a7e4-adb75fec7abe

Approvals / Standards

Reference standard	EN 61984:2009-06
Certifications	EAC

General ordering information

EAN13 code	8015747059244
-------------------	---------------

Packaging Information

Packaging length	325,00 mm
Packaging height	280,00 mm
Packaging width	315,00 mm
Packaging weight	16,00 kg
Packaging volume	28,67 dm ³
Packaging description	Carton box
Packaging quantity	20 Pcs
Packaging EAN code	8015747109772
Sub-packaging weight	0,80 kg
Sub-packaging description	Plastic bag
Sub-packaging quantity	1 Pcs
Sub-packaging EAN barcode	8015747225885

Part number

MNZ 24 PV



Notes

Dimensions shown in mm are not binding and may be changed without notice.

California Proposition 65 Information



WARNING

This product can expose you to lead and its compounds, known to the State of California to cause cancer and/or reproductive toxicity. For more information go to www.P65Warnings.ca.gov.
